## LIUGONG



G

3

ME

-



TOUGH WORLD. TOUGH EQUIPMENT.

## DW90A SPECIFICATIONS >>>

ENGINE	
Emission Regulation	Tier 3 / Stage III
Manufaturer	Yuchai
Model	YC6K520
Rated Power	382 kW (512 hp / 519 ps) @ 1,900 rpm
Peak Torque	2,400 N·m /1,100-1,500 rpm
Displacement	12.939 L
Number of Cylinders	6

TRANSMISSION	
Model	Allison 4800RS
Max. Speed	37 km/h
Retarder Model	Hydraulic Retarder

AXLE	
Front Axle Rated Load	20,000 kg
Rear Axle Rated Load	35,000*2 kg
Suspension Form	Leaf Spring
Max. Traction Force	320 kN
Max. Gradeability	≥32%

BRAKING	
Service Brake	Double Loop
Auxiliary Brake	Engine In-cylinder Brake
Service Braking Gradeability (load)	>25%
Park Braking Gradeability (load)	>15%
Pressure	10 bar
Air Tank Capacity	210 L

STEERING	
Steering System	Full Hydraulic Steering
System Pressure	16 MPa
Turn Radius	≤11,000 mm
HOIST SYSTEM	
Raise Time	≤ 21 s
Lower Time	≤ 21 s
System Pressure	22 MPa
CARRIER	
Carriage Size	6,370 mm*3,140 mm*1,680 mm
Rotate Angle	48°
Struck Capacity	30 m <sup>3</sup>
Heaped Capacity	36 m <sup>3</sup>

TIRE AND RIM	
Drive Type	6x4
Tire Size	1400RS 25 36PR NHS
Rim	10.0/2.0-25

DIMENSIONS	
Overall Length	9,370 mm
Overall Width	3,575 mm
Overall Height	3,900 mm
Loading Height	3,870 mm
Wheel Base	3,800 mm+1,550 mm
Wheel Tread	2,765 mm + 2,525 mm
Min. Ground clearance	365 mm
Fuel Tank Capacity	600 L







Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China T: +86 772 3886124 E: overseas@liugong.com www.liugong.com 10/2024 Designed by LiuGong

Specifications and designs are subject to change without notice. Machines shown may include optional equipment. LiuGong standard and optional equipment may vary from region to region. Please consult your LiuGong dealer for information specific to your area. Engine power kW is converted to horsepower (1 kW=1.3596 ps and 1 kW=1.3410 hp) in this file.